Invotech Selection Software

REFRIGERANT	R404A

Operation Conditions

Evaporating Temperature(℃):	-25.0
Condensing Temperature(℃):	45.0
Liquid subcooling:	0.0
Suction Superheat:	43.3

Required Capacity(Kw):

Compressor Selected: YM200E1G-100

PERFORMANCE AT SPECIFIED OPERATING POINT	
Capacity (KW)	11.44
Power Input (KW)	7.67
COP	1.49
Current (A)	14.7

CPMPRESSOR MECHANICAL AND PHYSICAL DATA	
Length/Width/Height (mm)	260/244/508
Weight (kg)	54
Stub Suction (inch)	1 1/8
Stub Discharge (inch)	7/8
Base mounting (hole dia)	190X190(8.5)
Oil type	POE
Initial charge of oil quantity (L)	3.0
Recharge of oil quantity (L)	2.8
High Side PS Max., (MPa)	3.2
Low Side PS Max., (MPa)	2.0
Displacement(m^3/h)	32.9

COMPRESSOR ELECTRICAL DATA	
Electricity	380V/50Hz/3P
Standard Conditions	-6.7/48.9/11.1/0
Normal Power (HP)	12
Normal Capacity (□)	19536
Normal Power input(□)	9671
Normal COP(□/□)	2.02
Normal Current(□)	16.3
Locked Rotor Current(□)	121
Maximum operating current(□)	26.5

Model: YM200E1G-100 Refrigerant: R404A

Suction Superheat: 43.3 Liquid subcooling: 0.0

Capacity(KW)

Tc\Te	-30	-25	-20	-15	-10	-5	0	5	10	
10	14.35	17.46	21.31	25.96	31.51					
15	13.42	16.42	20.09	24.5	29.75					
20	12.61	15.5	18.99	23.17	28.12	33.93				
25	11.89	14.67	17.98	21.92	26.57	32.02	38.36			
30	11.22	13.88	17.02	20.72	25.07	30.16	36.07	42.9	50.74	
35	10.56	13.11	16.07	19.53	23.58	28.31	33.8	40.14	47.43	
40	9.87	12.31	15.09	18.31	22.06	26.43	31.49	37.35	44.09	
45		11.44	14.05	17.04	20.49	24.49	29.13	34.5	40.69	
50			12.92	15.66	18.81	22.45	26.67	31.55	37.19	
55				14.15	17	20.28	24.07	28.47	33.55	
60					15.02	17.93	21.3	25.21	29.75	
65						15.38	18.32	21.75	25.74	

Power Input(KW)

Tc\Te	-30	-25	-20	-15	-10	-5	0	5	10	
10	4.07	4.25	4.47	4.72	5					
15	4.4	4.61	4.84	5.1	5.38					
20	4.77	5	5.25	5.53	5.82	6.12				
25	5.18	5.43	5.71	6	6.31	6.62	6.93			
30	5.62	5.91	6.22	6.53	6.85	7.17	7.49	7.8	8.1	
35	6.12	6.44	6.78	7.12	7.45	7.79	8.11	8.43	8.73	
40	6.66	7.03	7.4	7.76	8.12	8.48	8.81	9.13	9.43	
45		7.67	8.08	8.48	8.87	9.24	9.59	9.92	10.23	
50			8.82	9.26	9.68	10.08	10.45	10.79	11.11	
55				10.12	10.57	11	11.39	11.76	12.08	
60					11.55	12.01	12.43	12.81	13.15	
65						13.1	13.56	13.97	14.33	

Model: YM200E1G-100 Refrigerant: R404A

Suction Superheat: 43.3 Liquid subcoolling: 0.0

Current(A)

Tc\Te	-30	-25	-20	-15	-10	-5	0	5	10	
10	10.61	10.77	10.99	11.25	11.57					
15	10.92	11.12	11.36	11.65	11.98					
20	11.29	11.52	11.8	12.11	12.46	12.83				
25	11.7	11.99	12.31	12.65	13.02	13.41	13.81			
30	12.19	12.53	12.9	13.28	13.68	14.09	14.51	14.92	15.34	
35	12.76	13.16	13.57	14	14.44	14.88	15.32	15.75	16.17	
40	13.41	13.87	14.35	14.83	15.31	15.78	16.25	16.7	17.13	
45		14.7	15.23	15.77	16.3	16.82	17.32	17.79	18.24	
50			16.24	16.84	17.42	17.99	18.53	19.04	19.51	
55				18.04	18.69	19.31	19.89	20.44	20.95	
60					20.1	20.78	21.42	22.01	22.55	
65						22.42	23.12	23.76	24.35	

Mass Flow(Kg/h)

Tc\Te	-30	-25	-20	-15	-10	-5	0	5	10	
10	284.63	355.78	438.39	536.12	652.67					
15	279.16	349.4	431	527.64	643.01					
20	275.15	344.6	425.32	521	635.31	771.94				
25	272.15	340.93	420.9	515.74	629.14	764.76	926.29			
30	269.72	337.96	417.31	511.44	624.04	758.78	919.35	1109.41	1332.67	
35	267.41	335.25	414.1	507.65	619.58	753.57	913.29	1102.43	1324.67	
40	264.79	332.34	410.83	503.93	615.32	748.67	907.68	1096.02	1317.38	
45		328.81	407.05	499.82	610.8	743.66	902.08	1089.75	1310.35	
50			402.33	494.9	605.59	738.08	896.05	1083.17	1303.13	
55				488.72	599.25	731.49	889.13	1075.84	1295.3	
60					591.33	723.46	880.89	1067.31	1286.39	
65						713.53	870.89	1057.14	1275.98	

Invotech Selection Software

REFRIGERANT	R404A

Operation Conditions

Evaporating Temperature(□):	-8.0
Condensing Temperature(□):	45.0
Liquid subcooling:	0.0
Suction Superheat:	26.3

Required Capacity(Kw):

Compressor Selected:	YM200E1G-100

PERFORMANCE AT SPECIFIED OPERATING POINT

Capacity (KW)	22.02
Power Input (KW)	9.02
COP	2.44
Current (A)	16.51

CPMPRESSOR MECHANICAL AND PHYSICAL DATA

Length/Width/Height (mm)	260/244/508
Weight (kg)	54
Stub Suction (inch)	1 1/8
Stub Discharge (inch)	7/8
Base mounting (hole dia)	190X190(8.5)
Oil type	POE
Initial charge of oil quantity (L)	3.0
Recharge of oil quantity (L)	2.8
High Side PS Max., (MPa)	3.2
Low Side PS Max., (MPa)	2.0
Displacement(m^3/h)	32.9

COMPRESSOR ELECTRICAL DATA

Electricity	380V/50Hz/3P
Standard Conditions	-6.7/48.9/11.1/0
Normal Power (HP)	12
Normal Capacity (□)	19536
Normal Power input(□)	9671
Normal COP(□/□)	2.02
Normal Current(□)	16.3
Locked Rotor Current(□)	121
Maximum operating current(□)	26.5

Model: YM200E1G-100 Refrigerant: R404A

Suction Superheat: 26.3 Liquid subcooling: 0.0

Capacity(KW)

Tc\Te	-30	-25	-20	-15	-10	-5	0	5	10	
10	14.35	17.46	21.31	25.96	31.51					
15	13.42	16.42	20.09	24.5	29.75					
20	12.61	15.5	18.99	23.17	28.12	33.93				
25	11.89	14.67	17.98	21.92	26.57	32.02	38.36			
30	11.22	13.88	17.02	20.72	25.07	30.16	36.07	42.9	50.74	
35	10.56	13.11	16.07	19.53	23.58	28.31	33.8	40.14	47.43	
40	9.87	12.31	15.09	18.31	22.06	26.43	31.49	37.35	44.09	
45		11.44	14.05	17.04	20.49	24.49	29.13	34.5	40.69	
50			12.92	15.66	18.81	22.45	26.67	31.55	37.19	
55				14.15	17	20.28	24.07	28.47	33.55	
60					15.02	17.93	21.3	25.21	29.75	
65						15.38	18.32	21.75	25.74	

Power Input(KW)

Tc\Te	-30	-25	-20	-15	-10	-5	0	5	10	
10	4.07	4.25	4.47	4.72	5					
15	4.4	4.61	4.84	5.1	5.38					
20	4.77	5	5.25	5.53	5.82	6.12				
25	5.18	5.43	5.71	6	6.31	6.62	6.93			
30	5.62	5.91	6.22	6.53	6.85	7.17	7.49	7.8	8.1	
35	6.12	6.44	6.78	7.12	7.45	7.79	8.11	8.43	8.73	
40	6.66	7.03	7.4	7.76	8.12	8.48	8.81	9.13	9.43	
45		7.67	8.08	8.48	8.87	9.24	9.59	9.92	10.23	
50			8.82	9.26	9.68	10.08	10.45	10.79	11.11	
55				10.12	10.57	11	11.39	11.76	12.08	
60					11.55	12.01	12.43	12.81	13.15	
65						13.1	13.56	13.97	14.33	

Model: YM200E1G-100 Refrigerant: R404A

Suction Superheat: 26.3 Liquid subcoolling: 0.0

Current(A)

Tc\Te	-30	-25	-20	-15	-10	-5	0	5	10	
10	10.61	10.77	10.99	11.25	11.57					
15	10.92	11.12	11.36	11.65	11.98					
20	11.29	11.52	11.8	12.11	12.46	12.83				
25	11.7	11.99	12.31	12.65	13.02	13.41	13.81			
30	12.19	12.53	12.9	13.28	13.68	14.09	14.51	14.92	15.34	
35	12.76	13.16	13.57	14	14.44	14.88	15.32	15.75	16.17	
40	13.41	13.87	14.35	14.83	15.31	15.78	16.25	16.7	17.13	
45		14.7	15.23	15.77	16.3	16.82	17.32	17.79	18.24	
50			16.24	16.84	17.42	17.99	18.53	19.04	19.51	
55				18.04	18.69	19.31	19.89	20.44	20.95	
60					20.1	20.78	21.42	22.01	22.55	
65						22.42	23.12	23.76	24.35	

Mass Flow(Kg/h)

Tc\Te	-30	-25	-20	-15	-10	-5	0	5	10	
10	284.63	355.78	438.39	536.12	652.67					
15	279.16	349.4	431	527.64	643.01					
20	275.15	344.6	425.32	521	635.31	771.94				
25	272.15	340.93	420.9	515.74	629.14	764.76	926.29			
30	269.72	337.96	417.31	511.44	624.04	758.78	919.35	1109.41	1332.67	
35	267.41	335.25	414.1	507.65	619.58	753.57	913.29	1102.43	1324.67	
40	264.79	332.34	410.83	503.93	615.32	748.67	907.68	1096.02	1317.38	
45		328.81	407.05	499.82	610.8	743.66	902.08	1089.75	1310.35	
50			402.33	494.9	605.59	738.08	896.05	1083.17	1303.13	
55				488.72	599.25	731.49	889.13	1075.84	1295.3	
60					591.33	723.46	880.89	1067.31	1286.39	
65						713.53	870.89	1057.14	1275.98	