

MAER	型号 MODEL	YDWF102L70P4-753N-630 S
	品号 ITEM NO	
	客户代号CUSTOMER CODE	
	产品类型PRODUCT TYPE	External rotor axial flow fan
	产品认证APPROVALS	CE、CQC






PS: Fan working performance tested with Maer wall plate, and under standard atmospheric pressure at 20 ℃.


Condition of use:

1）voltage and frequency：1～ 220 V±5 %， 50 Hz。
2）Qualification requirements: Terminal block, the recommended standard of lead wire is not less than 0.75 mm².
3）Installation position: vertical or upward.
4) ambient temperature:-40～70℃。

The external wiring diagram:



Wiring diagram:



Performance parameters at key point:

	psf	I	P1	n	Q	Note
	(pa)	(A)	(W)	(r/min)	(m³/h)	
①	0	3.18	703	1398	11224	
②	73	3.73	824	1370	9836	
③	120	4.03	892	1349	8506	MAX EFF.
④	156	4.39	969	1320	7082	IMAX

Test data at free ：

connection	UAC (V)±5%	f (Hz)	P1 (W) ±10%	I (A)±10%	n (r/min) ±10%	Noise dB(A)
	1~220	50	790	3.6	1400	76

Mark 1(主唛)

MAER MOTORS & FANS AXIAL FAN MOTOR
MODEL:YDWF102L70P4-753N-630 SUCTION
VOLTAGE:1～220V/50HZ
N.W/G.W. / KG
MEAS:67X67X24 CM
CL.F WITH TERMINAL BOX
EAC
xxxxxxxx

Mark 2(副唛)

Вентилятор
Модель: YDWF102L70P4-753N-630 S
Изготовитель: Zhe Jiang MaEr Fan Motor CO.,LTD.
Адрес: NO.333 CHUANGYE ROAD,CHANGAN TOWN,HAINING CITY,ZHEJIANG,CHINA
Товарный знак: MAER
Сделано: KHP
Произведено: 2023
EAC

Technical specification:

1.All parts of fan should be properly assembled, no oil or dirt on the surface, no obvious distortion, mechanical damage and other defects.
2.Fan rotation is flexible, no delay, no operation sound, no scratch and other undesirable phenomena.
3.The safety requirement of fan is performed according to GB12350-2009, the electrical strength is 1800V.S, and the insulation resistance is not less than 100MΩ at room temperature.
4.Motor insulation class, F CLASS.
5.Motor protection level, IP54, fan protection level, IP2X.
6.The fan balance level is:1400±10%r/min high than G6.3, vibration value is less than 5.4mm/s.
7.630 concave net cover N100.
8.Built in thermal protector.
9.With Terminal block.Cassette foam.
10.With"EAC" English trademark,With"EAC" English mark1 and mark2 .
11.With TPI bearing.

Nameplate

YDWF102L70P4-753N-630 S
1～220V/50Hz 892W 4.03A 1349r/min @ 120Pa
20 μF/450V CL.F IP54 2023/07
EAC

版本/Ver.		Page 1		
重量/WG.	Kg	签名/Name	日期/Date	
绘图/Drawing				
审核/Checked				
批准/Approved				
客户确认/Customer confirmation				

浙江马尔风机有限公司
MaEr Fan Motor ZHEJIANG MAER FAN MOTOR CO.,LTD.
产品规格书
Product Specification

型号/Model	YDWF102L70P4-753N-630 S
品号 P/N	